









WEIGHT OF DETAILS (APPROXIMATE WEIGHTS)

Diameter of Chain										
		Joining Shackle Kenter	Joining Shackle Type D	Anchor Shackle Type D	Swivel Shackle	Swivel	Swivel Set (4 Links)	Common Link	Enlarged Link	End Link
inch	mm	kg	kg	kg	kg	kg	kg	kg	kg	kg
13/16	20.5	1	2	3	–	4	8.1	0.8	1.1	1.1
7/8	22	2	3	4	–	4	8.6	0.9	1.2	1.3
15/16	24	2	3	5	–	5	11.4	1.2	1.7	1.8
1	26	3	4	6	–	8	16.2	1.6	2.2	2.2
1-1/8	28	4	5	8	–	11	21.4	1.9	2.8	2.9
1-3/16	30	4	6	9	–	11	23.1	2.4	3.2	3.3
1-1/4	32	5	7	11	–	15	29.7	2.9	3.9	4.0
1-5/16	34	6	10	14	–	19	36.8	3.4	4.7	5.0
1-7/16	36	7	11	16	–	19	39.9	4.0	5.5	5.9
1-1/2	38	8	12	18	37	24	47.7	4.7	6.1	6.8
1-9/16	40	9	13	20	41	24	51.7	5.5	7.1	8.0
1-5/8	42	11	17	25	52	32	64.8	6.4	8.4	9.6
1-3/4	44	13	19	27	58	39	77.6	7.4	10.0	11.2
1-13/16	46	14	21	30	63	39	83.5	8.5	11.5	13.0
1-7/8	48	15	23	34	69	49	100	9.8	13.1	15.0
2	50	18	29	41	80	57	115	11	15	17
2-1/16	52	20	31	45	90	57	124	13	17	20
2-1/8	54	20	34	50	100	67	141	14	19	22
2-3/16	56	24	38	54	100	67	148	16	21	23
2-5/16	58	28	44	65	128	80	168	17	23	25
2-3/8	60	28	48	70	140	95	191	19	25	27
2-7/16	62	33	52	76	140	95	202	21	28	30
2-1/2	64	38	57	82	155	112	231	23	31	34
2-5/8	66	38	66	94	180	130	261	25	34	38
2-11/16	68	44	70	101	180	130	273	27	37	42
2-3/4	70	44	75	108	200	152	307	30	40	45
2-7/8	73	51	87	124	250	172	348	34	45	52
3	76	58	99	141	315	194	393	40	50	59
3-1/16	78	65	106	150	315	194	409	42	55	63
3-3/16	81	74	119	171	375	220	458	46	61	70
3-5/16	84	84	134	193	425	242	508	52	68	78
3-7/16	87	94	150	218	475	270	564	58	75	86
3-9/16	90	105	167	243	540	300	623	64	82	95
3-5/8	92	105	175	256	570	325	669	68	88	100
3-3/4	95	115	200	290	610	350	733	75	98	112
3-13/16	97	135	210	305	610	350	754	80	102	120
3-15/16	100	150	230	335	680	385	827	88	112	130
4	102	150	243	350	770	420	891	93	120	138
4-3/16	107	175	285	410	830	495	1042	109	140	158
4-3/8	111	200	305	445	860	535	1150	120	160	175
4-1/2	114	225	325	475	900	570	1239	130	173	193
4-5/8	117	225	345	505	950	610	1332	142	185	210
4-7/8	124	267	380	550	1000	650	1465	160	210	235
5	127	315	420	600	1080	720	1632	182	235	260
5-3/16	132	370	480	675	1150	760	1790	205	260	305
5-3/8	137	390	550	750	1500	900	2030	230	285	330
5-9/16	142	450	650	900	1900	1100	2380	255	325	375
5-3/4	147	505	720	1055	2100	1200	2680	280	395	410
6	152	545	810	1200	2500	1400	2990	310	410	460
6-3/16	157	612	970	1550	2860	1590	3355	345	455	510
6-3/4	162	664	1065	1700	3250	1760	3699	379	500	560